

TSic™ - 506

High Resolution, High Precision, Rapid Response Temperature Sensor IC

Feature Sheet


Features

- Low cost, high resolution, precision temperature sensor
- Single-wire 11-bit digital serial signal output compatible with state-of-the-art μ P controllers
- Communication range > 10 meters
- Resolution: 0.034°C
- Accuracy: $\pm 0.1^\circ\text{C}$ over a span of 40°C
- Focused measurement range: -10 to $+60^\circ\text{C}$
- Signal read-out every 0.1s (other rates available on request)
- V+ supply voltage: 2.97 to 5.5V (industry standard); 3.3V or 5V ($\pm 10\%$) power supplies
- Package: 8-pin SOIC
- Low quiescent current: $< 80\mu\text{A}$ at 25°C with 3.3V – minimizes self-heating errors for applications such as wall-mounted thermostats
- System-on-a-chip based on advanced mixed-signal technology integrating precision temperature sensing bandgap reference with proportional-to-absolute-temperature (PTAT) output, digital signal processor (DSP) core, and electrically erasable memory (EEPROM)

Package Information

TSic™ 506F SOP8: 150mil, Standard SMT Package, SOIC, Based on IEC 191-2Q, Type 076E35 B.

Other packages available on demand: TSic™ 506F e-line; 3 pin THT package.



Pin	Name	Description
1	V+	Supply voltage (3.0-5.5V)
2	Signal	Temperature output signal
4	Gnd	Ground
3, 5-8	TP/NC	Test pin / NC Do not connect

Brief Description

The TSic™ temperature sensor IC family are fully tested and calibrated sensors with absolute measurement accuracy on delivery – no further calibration needed. The TSic™ combines outstanding accuracy with long term stability, yet it is very simple to use.

The TSic™ series is specifically designed for high performance, cost-effective solutions for sensing temperature in building automation, automotive, industrial, office automation, white goods and low-power/mobile applications.

TSic™ employs a high precision bandgap reference with PTAT output; a low-power, precision ADC; and an on-chip DSP core with EEPROM to precisely calibrate the output temperature signal. The TSic™ series includes ICs with two linear analog signal output options, such as standard 0~1V_{out} (V₊ = 2.97V to 5.5V) or ratiometric (10~90% of V₊; i.e., 0.5~4.5V_{out} @ V₊ = 5V) or the digital serial output signal for interfacing with μ P controllers.

Benefits

- **Several accuracy classes available with 100% upward compatibility**
- **No calibration by customer needed; absolute calibration specified**
- **Simple to integrate, reducing cost and time for application-development**
- **Fast data measurement – optimal for temperature control**
- **Packages for standard SMD, THT or application specific assembly**
- **Very low power consumption – ideal for mobile and standard applications**
- **Field reconfiguration/recalibration option available (high volume customers only)**
- **Outstanding long term stability**



INNOVATIVE SENSOR TECHNOLOGY



TSic™ - 506

High Resolution, High Precision, Rapid Response Temperature Sensor IC

Feature Sheet

Absolute Maximum Ratings

PARAMETER	MIN	TYP	MAX	UNITS
Supply Voltage (V+)	-0.3		6.0	V
Voltages at Analog I/O Pins (V _{INA} , V _{OUTA})	-0.3		V _{DDA} +0.3	V
Storage Temperature Range (T _{stor})	-50		150	°C

Temperature Accuracy

PARAMETER	MIN	TYP	MAX	UNITS
<i>Focused Range Device for -10° to 60°C</i>				
+5 to +45 °C	-0.1	±0.05	0.1	°C ¹
-5 to +5, +45 to +55 °C	-0.1	+0.1	+0.2	°C ¹
-10 to -5, +55 to +60 °C	0	+0.15	+0.3	°C ¹

¹ 3σ value; plus quantization error of 1 bit (0.034 °C).

Operating Conditions

PARAMETER	MIN	TYP	MAX	UNITS
Supply Voltage to Gnd (V+) ¹	2.97	5.0	5.5	V
Supply Current (I _{v+}) @ V+ = 3.3V, RT	30	45	80	μA
Ambient Temperature Range (T _{amb}) ²	-10		60	°C
Output Load Capacitance (C _L)		10	15	nF
External Capacitance Between V+ and Gnd (C _{V+}) ³	80	100	470	nF
Output Load Resistance Between Signal and Gnd (or V+)	2.5	10		KΩ

- With supply voltage 2.7V - 2.97V, accuracy is slightly reduced; below 2.7V, functionality is unknown.
- Output signal is limited to this ambient temperature (applies to calibration, offset and gain).
- Locate as close as possible to TSic's V+ and Gnd pins.

Output Examples for TSic™ Devices

		Temperature Measurement Range -10°C to 60°C or 14°F to 140°F (F = focused range device)		
		TSic-501F	TSic-503F	TSic-506F
Temp (°C)	Temp (°F)	Analog 0~1V	Analog Ratiometric 10~90% @ V+=5V	Digital
≤ -10	≤ 14	0.000	10.00% =0.500V	0x000
0	32	0.143	21.43% =1.072V	0x124
25	77	0.500	50.00% =2.500V	0x3FF
≥ 60	≥ 140	1.000	90.00% =4.500V	0x7FF

$$\text{Temperature} = (\text{Digital Signal}/2047*70 - 10) \text{ °C}$$



For further information:

ZMD America, Inc.
201 Old Country Road, Suite 204
Melville, NY 11747, USA
Phone +01 (631) 549-2666
Fax +01 (631) 549-2882

sales@zmda.com
www.zmd.biz

ZMD AG
Grenzstrasse 28
01109 Dresden, Germany
Tel.: +49 (0)351.8822.366
Fax: +49 (0)351.8822.337

sales@zmd.de
www.zmd.biz

ZMD Far East
Taipei World Center
Sinyi Road, Sec. 5, Suite 7A-03
Taipei 110, Taiwan
Phone +886 (2) 8786 1592
Fax +886 (2) 2723 3109

sales@zmd.de
www.zmd.biz

The information furnished here is believed to be correct and accurate; however, ZMD and IST shall not be liable to any licensee or third party for any damages, including, but not limited to, personal injury, property damage, loss of profits, loss of use, interruption of business or indirect, special, incidental, or consequential damages of any kind, in connection with or arising out of the furnishing, performance, or use of this technical data. No obligation or liability to any licensee or third party shall result from ZMD or IST's rendering of technical or other services.



INNOVATIVE SENSOR TECHNOLOGY



TSic™ - 506

High Resolution, High Precision, Rapid Response Temperature Sensor IC

Feature Sheet

The information furnished here is believed to be correct and accurate; however, ZMD and IST shall not be liable to any licensee or third party for any damages, including, but not limited to, personal injury, property damage, loss of profits, loss of use, interruption of business or indirect, special, incidental, or consequential damages of any kind, in connection with or arising out of the furnishing, performance, or use of this technical data. No obligation or liability to any licensee or third party shall result from ZMD or IST's rendering of technical or other services.